

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 July 2004 (01.07.2004)

PCT

(10) International Publication Number
WO 2004/054652 A2

(51) International Patent Classification⁷: **A61M 25/00**

(21) International Application Number:
PCT/US2003/039689

(22) International Filing Date:
11 December 2003 (11.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/318,907 13 December 2002 (13.12.2002) US

(71) Applicant: SCIMED LIFE SYSTEMS, INC. [US/US];
One Scimed Place, Maple Grove, MI 55311 (US).

(72) Inventor: VRBA, Anthony, C.; 18519-83rd Avenue
North, Maple Grove, MN 55311 (US).

(74) Agents: SEAGER, Glenn, M. et al.; Crompton, Seager &
Tufte, LLC, 1221 Nicollet Avenue, Suite 800, Minneapolis,
MN 55403 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DISTAL PROTECTION GUIDEWIRE WITH NIZINOL CORE



(57) Abstract: A guidewire having a proximal section, a distal section, and a transition section is disclosed. In one exemplary embodiment of the present invention, the proximal section may be formed of a relatively stiff, inelastic material, whereas the distal section may be formed of a relatively flexible, elastic material having superelastic properties. A coupling member may be placed adjacent to the transition section to secure the proximal and distal sections together.

WO 2004/054652 A2

DISTAL PROTECTION GUIDEWIRE WITH NITINOL CORE

Field of the Invention

The present invention relates generally to the field of intravascular guidewires. More specifically, the present invention pertains to guidewires having super-elastic properties.

Background of the Invention

Guidewires are frequently used to advance intravascular devices such as stent delivery catheters, angioplasty catheters, and atherectomy catheters within a patient's vasculature. Such devices generally include a stiff proximal section to facilitate pushability and torqueability, and a flexible distal section for improved trackability. In some cases, the distal section of the guidewire may have a reduced profile capable of placement beyond a lesion or other stenosis within the body.

One important aspect of guidewire designs is the ability of the distal section to undergo significant bending within the body without permanently deforming the guidewire. Kinking results when the stress within the guidewire exceeds the elastic limit of the material, causing the material to plastically deform. As a result, a residual strain is imparted to the guidewire preventing it from fully recovering to its original shape. In certain circumstances, the inability of the guidewire to return to its original shape may diminish the performance and durability characteristics of the guidewire.

Summary of the Invention

The present invention relates generally to guidewires having super-elastic properties. In an exemplary embodiment of the present invention, a guidewire comprises a proximal section formed of a first material, and a distal section formed of a second material different from the first material. The proximal section of the guidewire may be formed of a relatively stiff, inelastic material, whereas the distal section may be formed of a relatively flexible, elastic material. In some embodiments, the distal section may be formed of a super-elastic material such as nickel-titanium alloy. A coupling member may be attached to the guidewire adjacent a transition section, securing the proximal and distal sections together.

Brief Description of the Drawings

Figure 1 is a plan view of an intravascular guidewire in accordance with an exemplary embodiment of the present invention, showing an embolic protection filter advanced along the guidewire; and

Figure 2 is a plan view of an intravascular guidewire in accordance with another exemplary embodiment of the present invention.

Detailed Description of the Invention

The following description should be read with reference to the drawings, in which like elements in different drawings are numbered in like fashion. The drawings, which are not necessarily to scale, depict selected embodiments and are not intended to limit the scope of the invention. Although examples of construction, dimensions, and materials are illustrated for the various elements, those skilled in the art will recognize that many of the examples provided have suitable alternatives that may be utilized.

Figure 1 is a plan view of an intravascular guidewire in accordance with an exemplary embodiment of the present invention. Guidewire 10 includes a proximal section 12, a distal section 14, and a transition section 16 securing the proximal section 12 to the distal section 14. Guidewire 10 is configured to support one or more intravascular devices thereon, such as the embolic protection filter 46 illustrated in Figure 1.

The proximal section 12 of guidewire 10 may be formed of a relatively stiff, inelastic material to enhance the pushability and torqueability characteristics of the guidewire, and to support the weight of various intravascular devices (*e.g.* balloon catheters, stent delivery catheters, etc.) thereon. Proximal section 12 may be formed of a metal such as type 304V stainless steel or platinum.

The distal section 14 of guidewire 10 may be formed of a relatively flexible, elastic material configured to impart flexibility to the guidewire for enhanced tracking through the tortuous vasculature. The distal section 14 may be formed from a material having different mechanical properties than the proximal section 12 of the guidewire 10. For example, the distal section 14 may be formed from a material having a lower modulus of elasticity than the proximal section 12, thereby imparting greater flexibility to the distal section 14. In one exemplary embodiment, the distal section 14 may comprise a super-elastic and/or linear-elastic material such as nickel-

titanium alloy (Nitinol). Nickel-titanium alloy exhibits pseudo-elastic capabilities at body temperature (37°C), allowing it to undergo substantial bending with relatively little residual strain. Unlike more commonly used materials such as stainless steel, the use of super-elastic materials such as Nitinol allows the distal section 14 to bend significantly without permanently (*i.e.* plastically) deforming.

Guidewire 10 further includes a transition section 16 forming a joint between the proximal and distal sections 12, 14. As shown in Figure 1, for example, the distal end 20 of the proximal section 12 may be coupled to the proximal end 22 of the distal section 14, forming a butt joint therebetween. The proximal and distal sections 12, 14 of the guidewire 10 may be bonded together by adhesive, welding (*e.g.* resistance, laser, ultrasonic), soldering, brazing, or any other suitable bonding technique.

In certain embodiments, guidewire 10 may include a coupling member 24 further securing the proximal section 12 to the distal section 14. The coupling member 24 may comprise a tubular member or wire coil having an inner diameter configured to receive the distal end 20 of the proximal section 12 and the proximal end 22 of the distal section 14. The coupling member 24 may be formed from a metal or metal alloy, including stainless steel, nickel-titanium alloy, nickel-chromium alloy, nickel-chromium-iron alloy, nickel-chromium-molybdenum, cobalt alloy, or nickel. For example, in bonding a stainless steel proximal section 12 to a nickel-titanium distal section 14, a nickel-chromium-molybdenum based alloy such as INCONEL 625, ALLOY C276 or ALLOY B2 may be used. INCONEL 625 is commercially available from the California Fine Wire Company of Grover Beach, California. ALLOY C276 and B2 are commercially available from the Fort Wayne Metals Research Products Corporation of Fort Wayne, Indiana.

In an alternative embodiment, the coupling member 24 may comprise a polymeric material that can be heat shrunk adjacent the ends 20, 22 of the proximal and distal sections 12, 14. For example, a tubular segment formed of polytetrafluoroethylene (PTFE) can be placed adjacent the ends 20, 22 of the two sections 12, 14 and heated to a sufficient temperature, causing the material to flow onto the ends 20, 22. In yet another embodiment, the coupling member 24 may include a solder material that can be reflowed adjacent the ends 20, 22 of the proximal and distal sections 12, 14.

In those embodiments utilizing a coupling member 24, the ends 20, 22 of the proximal and distal sections 12, 14 may be tapered or reduced in diameter such that

the profile of the guidewire 10 at the transition section 16 is substantially similar to the profile of the proximal and distal sections 12, 14 immediately adjacent the transition section 16. As shown in Figure 1, for example, the ends 20, 22 of the proximal and distal sections 12, 14 may include a necked-down portion 26 reducing the outer diameter of the sections 12, 14 at the transition section 16.

The distal section 14 may also include a shaping ribbon 28. The shaping ribbon 28 connects the distal end 30 of the distal section 14 to a coil tip 34 disposed at the distal end 32 of the guidewire 10. The shaping ribbon 28 may be formed of metal (e.g. type 304V stainless steel), a polymer, or any other suitable material.

Coil tip 34 is generally circular in shape, and includes a proximal portion 36 forming a rearwardly facing shoulder, and a distal portion 38. The coil tip 34 may be substantially round, and may include a hydrophilic coating to reduce tissue damage within the body.

Guidewire 10 may also include a wire coil 40 disposed at least in part about the distal section 14. The wire coil 40 may be attached at a proximal end 42 to the distal section 14, and at a distal end 44 to the proximal portion 36 of coil tip 34. The wire coil 40 may be formed from a single, continuous strand of wire helically disposed about the distal section 14. In certain embodiments, the wire coil 40 may comprise a radiopaque material such as gold, platinum, or tantalum, allowing the operator to fluoroscopically judge the location of the guidewire 10 within the body.

An intravascular device such as the embolic protection filter 46 depicted in Figure 1 may be placed on the guidewire 10. The embolic protection filter 46 may include a tubular base member 48, which allows the filter 46 to slide and rotate about the guidewire 10. In use, the guidewire 10 may be percutaneously inserted into a blood vessel, and advanced to a desired location within the body (e.g. a coronary artery). Once positioned, the embolic protection filter 46 can then be advanced over the guidewire 10 via a delivery catheter, and placed at a location downstream a lesion or other stenosis within the vessel. An intravascular device such as an angioplasty balloon can then be advanced along the guidewire 10 to a location upstream of the embolic protection filter 46 to perform a therapeutic procedure such as percutaneous transluminal coronary angioplasty. A stent may also be advanced along the guidewire 10 and deployed within the body, if desired.

In an alternative embodiment (not shown), the embolic protection filter 46 may be fixedly secured to the distal section 14 of the guidewire 10 prior to insertion

within the patient. In a fixed configuration, the guidewire 10 and attached embolic protection filter are both loaded into the delivery catheter prior to being inserted into the body. The guidewire 10 and attached filter are simultaneously inserted into the body, and then advanced to the site of the lesion. Once positioned distal the lesion, the guidewire can then be used to advance other intravascular devices to the site.

To collect embolic debris dislodged during the therapeutic procedure, embolic protection filter 46 may include a filter mesh or membrane 50 coupled to a proximal support hoop 52. The proximal support hoop 52 forms a mouth or opening on the embolic protection filter 46, and is biased to radially expand within the vessel when removed from the delivery catheter. The filter mesh or membrane 50 may include several openings or pores 54 configured to filter embolic debris while permitting the perfusion of blood through the blood vessel. A tether line 56 connects the embolic protection filter 46 to the tubular base member 48.

Embolic protection filter 46 may further include a nose cone 58. Nose cone 58 is formed from an enlarged diameter distal portion of the tubular base member 48. The nose cone 58 is tapered distally to provide a relatively uniform profile transition between the proximal end 42 of the wire coil 40 and the embolic protection filter 46. A reduced inner diameter portion 60 on the distal end 62 of the nose cone 58 is adapted to slide over the proximal end 42 of the wire coil 40. In use, the proximal end 42 of the wire coil 40 acts as a distal stop, preventing the embolic protection filter 46 from being advanced beyond the distal end 32 of the guidewire 10.

Figure 2 is a plan view of an intravascular guidewire in accordance with another exemplary embodiment of the present invention. Guidewire 110 includes a proximal section 112, a distal section 114, and a transition section 116. As with the embodiment described above with respect to Figure 1, guidewire 110 is configured to support one or more intravascular devices thereon.

The proximal section 112 of guidewire 110 may comprise a relatively stiff, inelastic material (*e.g.* type 304V stainless steel), whereas the distal section 114 may comprise a relatively flexible, super-elastic material such as nickel-titanium alloy. The distal end 120 of the proximal section 112 may include a notch configured to align with a correspondingly dimensioned notch on the proximal end 122 of the distal section 114. Together, the notches form a lap joint 162 between the proximal and distal sections 112, 114.

A coupling member 124 may also be placed adjacent the ends 120, 122 of the proximal and distal sections 112, 114 at the transitional section 116. In those embodiments utilizing a coupling member 124, the ends 120, 122 of the proximal and distal sections 112, 114 may be tapered or reduced in diameter such that the profile of the guidewire 110 at the transition section 116 is substantially similar to the profile of the proximal and distal sections 112, 114 immediately adjacent the transition section 116.

A wire coil 140 may be placed about a portion of the distal section 114. Wire coil 140 has a proximal end 142 and a distal end 144. The proximal end 142 of wire coil 140 may be attached to a shoulder 164 located on the distal section 114 of the guidewire 110. The distal end 144 of wire coil 140, in turn, may be attached to the proximal portion 136 of the coil tip 134. A shaping ribbon 128 connecting the distal end 130 of the distal section 114 to the proximal portion 136 of the coil tip 134 may also be used, if desired.

Guidewire 110 further includes a distal stop 166 disposed about a portion of the distal section 114. Distal stop 166 comprises an object having an outer diameter slightly larger than the inner diameter of the intravascular device. In use, the distal stop 166 prevents movement of the intravascular device beyond the distal end 132 of the guidewire 110.

Attachment of the distal stop 166 to the guidewire 110 may be accomplished by any number of suitable attachment means, including crimping, soldering, brazing, welding, adhesion or any combination thereof. Furthermore, the distal stop 166 may be formed from any number of suitable materials, such as stainless steel or nickel-titanium alloy. In one implementation, the distal stop 166 may be formed by heat bonding a polymeric object about the distal section 114.

Although the exemplary embodiments illustrated in Figures 1-2 depict a guidewire 10, 110 having a solid core (*i.e.* solid cross-section), it should be understood that other configurations are possible without deviating from the scope of the invention. For example, the proximal and distal sections may have a hollow cross-sectional area, forming a guide catheter or the like.



Having thus described the several embodiments of the present invention, those of skill in the art will readily appreciate that other embodiments may be made and used which fall within the scope of the claims attached hereto. Numerous advantages of the invention covered by this document have been set forth in the foregoing

description. It will be understood that this disclosure is, in many respects, only illustrative. Changes may be made in details, particularly in matters of shape, size and arrangement of parts without exceeding the scope of the invention.

What is claimed is:

1. A guidewire, comprising:
an elongate shaft including a proximal section, a distal section, and a transition section, the proximal section comprising a first material, the distal section comprising a second material different from the first material;
a coupling member attached adjacent to the transition section, said coupling member configured to secure the proximal section to the distal section; and
an embolic protection filter disposed on the shaft.
2. The guidewire of claim 1, wherein the proximal section is comprised of stainless steel.
3. The guidewire of claim 1, wherein the distal section is comprised of a super-elastic material.
4. The guidewire of claim 1, wherein the distal section is comprised of a linear-elastic material.
5. The guidewire of claim 1, wherein the distal section is comprised of nickel-titanium alloy.
6. The guidewire of claim 1, wherein the transition section forms a joint between the proximal and distal sections.
7. The guidewire of claim 6, wherein said joint is a butt joint.
8. The guidewire of claim 6, wherein said joint is a lap joint.
9. The guidewire of claim 1, wherein the transition section includes a necked-down portion.
10. The guidewire of claim 1, wherein the coupling member comprises a tubular member.

11. The guidewire of claim 1, wherein the coupling member comprises a nickel-chromium-molybdenum alloy tube.
12. The guidewire of claim 1, wherein the coupling member comprises a polymeric member heat shrunk adjacent to the transition section.
13. The guidewire of claim 1, further comprising a wire coil disposed about a portion of said distal section.
14. The guidewire of claim 13, wherein said wire coil is formed from a single continuous strand of wire helically disposed about a portion of said distal section.
15. The guidewire of claim 13, wherein said wire coil comprises a radiopaque material.
16. The guidewire of claim 1, further comprising a coil tip.
17. The guidewire of claim 16, wherein said coil tip includes a hydrophilic coating.
18. The guidewire of claim 1, further comprising a safety ribbon.
19. The guidewire of claim 1, further comprising a distal stop disposed about a portion of said distal section.



THIS PAGE BLANK (USPTO)

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 July 2004 (01.07.2004)

PCT

(10) International Publication Number
WO 2004/054652 A3

(51) International Patent Classification⁷: **A61M 25/01**,
A61F 2/01

(21) International Application Number:
PCT/US2003/039689

(22) International Filing Date:
11 December 2003 (11.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/318,907 13 December 2002 (13.12.2002) US

(71) Applicant: **SCIMED LIFE SYSTEMS, INC.** [US/US];
One Scimed Place, Maple Grove, MI 55311 (US).

(72) Inventor: **VRBA, Anthony, C.**; 18519-83rd Avenue
North, Maple Grove, MN 55311 (US).

(74) Agents: **SEAGER, Glenn, M.** et al.; Crompton, Seager &
Tufte, LLC, 1221 Nicollet Avenue, Suite 800, Minneapolis,
MN 55403 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

(88) Date of publication of the international search report:
12 August 2004

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: **DISTAL PROTECTION GUIDEWIRE WITH NIZINOL CORE**



(57) Abstract: A guidewire (10) having a proximal section (12), a distal section (14), and a transition section (16) is disclosed. The proximal section may be formed of a relatively stiff, inelastic material, whereas the distal section may be formed of a relatively flexible, elastic material having superelastic properties. A coupling member may be placed adjacent to the transition section to secure the proximal and distal sections together. An intravascular device such as an embolic protection filter (46) is placed on the guidewire.

WO 2004/054652 A3

INTERNATIONAL SEARCH REPORT

PCT/US 03/39689

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61M25/01 A61F2/01

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61M A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 99/22673 A (GAMBALE RICHARD A ; BARD INC C R (US); GRAY WILLIAM (US)) 14 May 1999 (1999-05-14) page 6, line 9 - page 7, line 35 page 10, line 38 - page 12, line 31; figures 1-5,11,12	1-10, 13-19
Y	EP 0 838 230 A (TERUMO CORP) 29 April 1998 (1998-04-29) the whole document	1-10, 13-19
A	EP 1 238 639 A (BAVARIA MED TECH) 11 September 2002 (2002-09-11) the whole document	1-19
A	EP 0 806 220 A (TARGET THERAPEUTICS INC) 12 November 1997 (1997-11-12) paragraph '0040! - paragraph '0060!; figures 1-5	1-19

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

16 June 2004

Date of mailing of the international search report

24/06/2004

Name and mailing address of the ISA

European Patent Office, P.O. Box 1818, D-50452 Cologne, Germany
Tel: +49 228 181-11, Fax: +49 228 181-1234

Authorized officer

INTERNATIONAL SEARCH REPORT

on on patent family members

PCT/US 03/39689

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
WO 9922673	A	14-05-1999	EP	1028671 A1	23-08-2000
			JP	2001521779 T	13-11-2001
			WO	9922673 A1	14-05-1999
			US	2003074019 A1	17-04-2003
<hr/>					
EP 0838230	A	29-04-1998	JP	3380691 B2	24-02-2003
			JP	10118005 A	12-05-1998
			JP	11057014 A	02-03-1999
			DE	69724903 D1	23-10-2003
			EP	1325763 A2	09-07-2003
			EP	0838230 A2	29-04-1998
			US	6001068 A	14-12-1999
<hr/>					
EP 1238639	A	11-09-2002	EP	1238639 A1	11-09-2002
<hr/>					
EP 0806220	A	12-11-1997	US	6488637 B1	03-12-2002
			AT	253953 T	15-11-2003
			AU	704689 B2	29-04-1999
			AU	1658697 A	06-11-1997
			CA	2200766 A1	31-10-1997
			DE	69726044 D1	18-12-2003
			EP	1287846 A2	05-03-2003
			EP	0806220 A2	12-11-1997
			JP	3181533 B2	03-07-2001
			JP	10033689 A	10-02-1998
			NO	971762 A	31-10-1997

THIS PAGE BLANK (USPTO)